

C Test Plugs



Web Page



WhatsApp



E-mail

TAPASAN C Test Plugs are used for testing and evacuation of pipelines with short pipe lengths. These are produced by vulcanizing SBR+NR rubber and high-strength fabrics. between -30°C and +70°C temperature resistant. Thanks to its extra short length, it can be easily used in house pipelines and short pipe distances.

*It can be produced with NBR rubber resistant to gas, petroleum and derivatives.

Product Code : CKTB



Connection
Type



Small By-pass
Design



Technical Detail
Label

Product Code	Size Usage Range		Max. Working Pressure	Deflated Plug Dimensions		By-pass Size
	Min. Diameter	Max. Diameter		Diameter	Lenght	
	(mm) / (inch)	(mm) / (inch)		(mm) / (inch)	(mm) / (inch)	
CKTB3040	30 / 1.1"	40 / 1.5"	2.5 / 36	29 / 1.1"	50 / 1.9"	1/8"
CKTB4050	40 / 1.5"	50 / 2"	2.5 / 36	38 / 1.4"	90 / 3.5"	1/8"
CKTB5075	50 / 2"	75 / 3"	2.5 / 36	48 / 1.8"	110 / 4.3"	1/4"
CKTB60	60 / 2.4"		2.5 / 36	58 / 2.2"	120 / 4.7"	1/4"
CKTB75	75 / 3"		2.5 / 36	68 / 2.6"	140 / 5.5"	1/2"
CKTB70100	70 / 2.8"	100 / 4"	2.5 / 36	68 / 2.6"	185 / 7.2"	1/2"
CKTB100	100 / 4"		2.5 / 36	88 / 3.4"	160 / 6.2"	1/2"
CKTB100150	100 / 4"	150 / 6"	2.5 / 36	88 / 3.4"	185 / 7.2"	1/2"
CKTB150	150 / 6"		2.5 / 36	138 / 5.4"	160 / 6.2"	1"
CKTB150200	150 / 6"	200 / 8"	2.5 / 36	138 / 5.4"	200 / 7.8"	1"
CKTB200250	200 / 8"	250 / 10"	2.5 / 36	180 / 7.0"	250 / 9.8"	1"
CKTB250300	250 / 10"	300 / 12"	2.5 / 36	182 / 7.1"	300 / 11.8"	1"
CKTB300	300 / 12"		2.5 / 36	282 / 11.1"	300 / 11.8"	1"
CKTB300350	300 / 12"	350 / 14"	2.5 / 36	282 / 11.1"	350 / 13.7"	1"